shafted hedge trimmers



Shindaiwa's line of shafted hedge trimmers provides optimum performance and durability for season after season of outstanding operation on even the toughest jobs and in the harshest conditions. And each one is covered by a 2-year

commercial warranty — dependability you can count on.




Carry the Legend™

877.9.TORQUE • www.shindaiwa.com

shafted hedge trimmers

AH254

- StaySharp™ chrome-plated 22" double-sided blades
- Articulating gear case 150° range with 11 positions
- Blades fold back onto shaft for easy storage
- Solid steel drive shaft
- High blade speed increases productivity and provides a clean cut
- Large blade tooth gap allows trimming of thicker branches
- Engine features chrome plated cylinder for extended service life
- Heavy-duty air filter element is easily accessible; no tools needed for maintenance
- Anti-vibration engine mount for reduced operator fatigue
- Fiberglass reinforced tank stand protects fuel tank



Displacement 24.5 cc Dry Weight 14 lbs. (6.3 kg) Blade Type Double-sided Shaft Length 57 in. (144.8 cm) 150° - 11 positions Range of Articulation Carburetor

Rotary **Fuel Capacity** 20 fl. oz (591 ml) Fuel 50:1 Ratio Fuel/mixing oil



AHS254

- StaySharp™ chrome-plated 22" double-sided blades
- Articulating gear case 135° range with 10 positions
- Solid steel drive shaft
- High blade speed increases productivity and provides a clean cut
- Large blade tooth gap allows trimming of thicker branches
- Engine features chrome plated cylinder for extended service life
- Heavy-duty air filter element is easily accessible; no tools needed for maintenance
- Anti-vibration engine mount for reduced operator fatigue
- THAT SHARMAN Fiberglass reinforced tank stand protects fuel tank
- Rubber over-molded front handle for more comfortable handling

The light and powerful mid-reach AHS254 is shorter in length than the AH254 and it's perfect for low hedges and shrubs, featuring StaySharp™ chrome-plated blades and an articulating gear case

Displacement Dry Weight Blade Type Shaft Length Range of Articulation Carburetor

Fuel Capacity Fuel 50:1 Ratio 24.5 cc 13.6 lbs. (6.2 kg) Double-sided 29 in. (73.7 cm) 135° - 10 positions

Rotary 20 fl. oz (591 ml) Fuel/mixing oil

Dealer imprint area.

shindaiwa®

Carry the Legend™

877.9.TORQUE • www.shindaiwa.com

MKT1020030 June 2010